

# Model Protea 4.24GS Four Channel Digital Graphic Equalizer Slave





## ARCHITECTS SPECIFICATIONS

#### Protea 4.24GS

The programmable graphic equalizer shall consist of four independent channels of 24 bit digital graphic equalization. Each channel shall consist of 28 bands centered on standard ISO frequencies at intervals of 1/3 octave and covering a frequency range of 31Hz to 16kHz. Frequency bands shall be activated by individual up and down tactile switches. The range of equalization per band shall be  $\pm 15 dB$  in 0.5dB increments. The equalizer shall have a gain of unity with all bands set at zero, and shall have a maximum in/out level of +20dBu. Frequency response shall be ±.25dB 20Hz to20kHz. Dynamic Range shall be greater than 100dB (unweighted) and SMPTE intermodulation distortion or THD shall be less than 0.01% at 1KHz, +20dBu. Input impedance shall be 18K ohms balanced. Output impedance shall be 200 ohms. Inputs and outputs shall be active (transformerless) balanced type on XLR and 1/4" phone jacks. Individual filters shall be of a constant Q reciprocal filter design. Boost and cut characteristics shall be fully symmetrical. Individual filters shall be accurate to within 3% of indicated center Frequency and shall be nonadjustable to insure long term accuracy. The equalizer shall also include on each channel an 18dB per octave high pass filter adjustable from 0.0Hz to 10.6KHz, an 18dB per octave low pass filter adjustable from 33Hz to 20.1KHz, a full function,

pre/post switchable compressor/limiter with adjustable threshold, ratio, attack and release controls, and a time alignment delay capable of a maximum of 341ms adjustable in 20us increments. LED indicators shall show signal present, clip and MIDI channel number. Channel gain shall be adjustable over a range of +6dB to infinity in 0.5db increments. Control of the unit shall be from the 4.24G, via the optional 4.24RD remote control, via RS-232 serial port using Ashly Protea System Software, or via MIDI. The equalizer shall weigh 13 lbs net and mount in a standard 19" rack using 2 spaces (3.50" high). The power requirement shall be 110-115VAC, 50-60Hz, 35W. The unit shall be an Ashly Audio Protea 4.24GS.

The optional remote controller shall operate all functions of the Protea unit using push-buttons and shall be phantom powered from the Protea unit so that no batteries or AC line cords are needed while controlling the Protea unit. Connections between the controller and Protea unit shall be accomplished using XLR connectors and standard mic cable. A 240 X 64 fluorescent backlit LCD display shall show all parameter, function and utility information. LED indicators shall show channel and mute conditions. The remote controller shall have a low profile for desk-top operation. The remote controller shall be the model Protea 4.24RD.

- 24 Bit A/D D/A Audio Resolution
- 24 Bit Digital Signal Processing
- Four 28-Band 1/3 Octave Channels of EQ
- Programmable Compressor/Limiter
- Programmable Delay
- Programmable High and Low Pass Filters
- Control From 4.24G, 4.24RD, MIDI or PC
- Balanced XLR and 1/4" Inputs and Outputs
- Linkable Channels
- Constant Q/Reciprocal Filter Design
- +/- 15dB Boost and Cut, 0.5dB increments
- 128 Preset Locations
- RS-232 Computer Interface
- Full MIDI Implementation
- 5-Year Worry-Free Warranty

## **General Specifications Protea 4.24GS**

INPUT Type: Active Balanced Impedance: 18 K ohms Max. Level: +20dBu

Pseudo-Balanced

±.25dB 20Hz-20kHz

200 ohms

+20dBu

>100dB

Threshold: -20dBu to +20 dBu Ratio: 1dB increments 1:1 to Infinity

(1:1, 1.5:1, 2:1, 5:1, 10:1, 20:1, 50:1, 100:1)

Attack: Release: 0.5ms to 50ms

COMPRESSOR/LIMITER

(.5, 1, 2, 5, 10, 20, 50ms) 10ms to 1 sec

33Hz to 20.1KHz

(10, 20, 50, 100, 200, 500ms, 1

Sec)

<.01% @ 1KHz, +20dBu

HPF

Range: 0Hz to 10.6Khz

**FILTERS** 

**OUTPUT** 

Max. Level:

Min. Load Impedance:

Frequency Response:

THD (20Hz-20kHz):

Dynamic Range:

Type:

Constant Q, Reciprocating Type:

Number: 4 X 28 Bandwidth: 1/3 Octave

Tolerance: ±3%

±15dB, 0.5dB Increments 341ms Range: Maximum Delay: Q: Fixed, 3.2 Increment: 20us

Power Requirements: 93-125VAC, 50-60Hz, 35W

(240VAC switchable) 24 Bit Input A to D Output D to A 24 Bit

LPF

Range:

**DELAY** 

**PROCESSOR** 


Shipping Weight: 13 lbs Processor 24 Bit 19"L x 3.5"H x 6"D Sample Rate 48KHz Dimensions: I/O Connectors: XLR, 1/4"

Notes: 1. 0 dBu = .775 V RMS

General Specifications: Protea 4.24RD

Shipping Weight: 5 lbs., Dimensions: 16.9"L x 1.65"H x 5.36"D, I/O Connectors: XLR, Power: Phantom

#### Protea 4.24GS (back)



### Protea 4.24RD (back)



### **Applications:**

PA Systems, Concerts, Outdoor Festivals, Churches, Sports Stadiums, Auditoriums, Studios, Dance/Night Clubs, Lecture Halls

#### Misc:

Protea System Software for PC control of the Protea 4.24G may be downloaded free from our website. Use it to control the 4.24G, 4.24GS and 2.24GS. Download it now to preview the capabilities of the Protea Series Graphic Equalizer products.

Ashly also manufactures a complete and comprehensive line of Parametric Equalizers, Electronic Crossovers, Power Amplifiers, Compressor-Limiters, Noise Gates, Mixers, and Amplifier Input Options. Please call or write for information on any of these Ashly Products.